













Product Description	Features	Material	Standard Size
Flexible Duct 	<ul style="list-style-type: none"> Used widely in air-conditioning ductwork. Central core is permanently bonded to a coated spring steel wire helix. Support a thick blanket of fiber glass insulation, providing a double seal (optional). 	<ul style="list-style-type: none"> Film: Reinforced metalized film Wire: corrosion resistant spring steel wire helix 	<ul style="list-style-type: none"> 100mm 150mm 200mm 250mm 300mm 350mm
KK Fiber Glass 	<ul style="list-style-type: none"> Used as multi-purpose thermal insulation. Sound attenuation. 	<ul style="list-style-type: none"> 10kg/m³ x 50mm x 1.2m x 30m 20kg/m³ x 25mm x 1.2m x 30m 16kg/m³ x 50mm x 1.2m x 15m 24kg/m³ x 25mm x 1.2m x 20m 32kg/m³ x 25mm x 1.2m x 20m 32kg/m³ x 50mm x 1.2m x 10m 	
Acoustic Panel 	<ul style="list-style-type: none"> Used as noise absorption at plant rooms. Suitable for air handling unit or similar applications. Designed for easy and quick installation. Can be custom made to fit various applications. 	<ul style="list-style-type: none"> Frame: 0.5mm perforated sheet. Insulation: 25mm, 32kg/m³ fiberglass. 	<ul style="list-style-type: none"> 44" x 20" Custom size available.
Duct Colar 	<ul style="list-style-type: none"> Used as connection between ductwork and flexible duct. Hassle-free design. Available in round and oval shape. 	<ul style="list-style-type: none"> 0.5mm Galvanised Steel. 	<ul style="list-style-type: none"> 100mm 150mm 200mm 250mm 300mm 350mm
Flexible Duct Connector 	<ul style="list-style-type: none"> Prevent transmission of vibration. Suitable to use between ductwork, air handling unit, fan connection or similar application. Steel side can be rolled to form TDC flange or clip joint. 	<ul style="list-style-type: none"> 0.5mm galvanized steel. PVC sloth or silicon. 	<ul style="list-style-type: none"> Depend on ductwork.

Product Description	Features	Material	Standard Size
Access Door 	<ul style="list-style-type: none"> • For easy access to ductwork maintenance and cleaning. • Internal insulated to attenuate noise, prevent condensation and heat loss. 	<ul style="list-style-type: none"> • Frame & Panel: 0.7mm galvanized steel. • Seal: PE foam gasket. • Door Lock: Aluminium or steel. • Insulation: 25mm, 32kg/m3 fiber glass. 	<ul style="list-style-type: none"> • N300mm x 300mm • N400mm x 400mm • N450mm x 450mm • Custom size available
Guide Vanes 	<ul style="list-style-type: none"> • Minimize pressure drop and noise generated. • Reduce turbulence. • Energy saving. 	<ul style="list-style-type: none"> • 1.0mm Galvanized Steel. • 1.2mm Galvanized Steel. 	<ul style="list-style-type: none"> • Custom size available.
Ductwork Fittings 	<ul style="list-style-type: none"> • Connection for ductwork. 	<ul style="list-style-type: none"> • Thickness depend on ductwork. 	<ul style="list-style-type: none"> • Custom size available.
TD-C & TD-F Corner Piece 	<ul style="list-style-type: none"> • Cost effective solution for ductwork connection. 	<ul style="list-style-type: none"> • 1.0mm Galvanized steel. • 1.2mm Galvanized Steel. 	-
Stud & Threaded Rod 	<ul style="list-style-type: none"> • Use for hanging ductwork. 	<ul style="list-style-type: none"> • Galvanized Steel. 	<ul style="list-style-type: none"> • Ø3/8 in (9.53mm) • Ø1½ in (3.81mm)

Product Description	Features	Material	Standard Size
<p>Quadrant Arm</p> 	<ul style="list-style-type: none"> • Volume control for manual volume damper. • With indicator. 	<ul style="list-style-type: none"> • 1.0mm Galvanized Steel. 	<p>-</p>
<p>Drop-in Anchor</p> 	<ul style="list-style-type: none"> • Used in medium to heavy duty application. • For solid concrete base material. • Ideal for overhead applications. • Fast, easy installation with excellent holding value. 	<ul style="list-style-type: none"> • Mild Steel. • Finishing: White Zinc Plated with half Knurling. 	<ul style="list-style-type: none"> • 5/16" x 10mm x 30mm • 3/8" x 12mm x 40mm