










DUCTWORK ACCESSORIES

Product Description	Features	Material	Standard Size
 <p>Flexible Duct</p>	<ul style="list-style-type: none"> Used widely in air conditioning ductwork. Central core is permanently bonded to a coated spring steel wire helix. Support a thick blanket of fiber glass insulation, providing a double seal (optional). 	<ul style="list-style-type: none"> Film: Reinforced metalized film Wire: corrosion resistant spring steel wire helix 	<ul style="list-style-type: none"> Ø 100mm Ø 150mm Ø 200mm Ø 250mm Ø 300mm Ø 350mm Ø 400mm
 <p>Fiber Glass</p>	<ul style="list-style-type: none"> Used as multi-purpose thermal insulation. Sound attenuation. 	<ul style="list-style-type: none"> 50mm, 10kg/m³ x 1.2m x 30m 25mm, 20kg/m³ x 1.2m x 30m 25mm, 24kg/m³ x 1.2m x 20m 50mm, 24kg/m³ x 1.2m x 10m 25mm, 32kg/m³ x 1.2m x 20m 50mm, 32kg/m³ x 1.2m x 10m 	
 <p>Acoustic Panel</p>	<ul style="list-style-type: none"> Used as noise absorption at plant rooms. Suitable for air handling unit or similar applications. Designed for easy and quick installation. Can be custom made to fit various applications. 	<ul style="list-style-type: none"> Frame: 0.5mm perforated sheet. Insulation: 25mm, 32kg/m³ fiberglass. 	<ul style="list-style-type: none"> 44" x 20" Custom size available.
 <p>Duct Colar</p>	<ul style="list-style-type: none"> Used as connection between ductwork and flexible duct. Hassle-free design. Available in round and oval shape. 	<ul style="list-style-type: none"> 0.5mm Galvanised Steel. 	<p>Standard Size</p> <ul style="list-style-type: none"> Ø 100mm Ø 150mm Ø 200mm Ø 250mm Ø 300mm Ø 350mm Ø 400mm
 <p>Flexible Duct Connector</p>	<ul style="list-style-type: none"> Prevent transmission of vibration. Suitable to use between ductwork, air handling unit, fan connection or similar application. Steel side can be rolled to form TDC flange or clip joint. 	<ul style="list-style-type: none"> 0.5mm galvanized steel. PVC cloth or silicon. 	<ul style="list-style-type: none"> Depend on ductwork.

Ductwork Accessories

Product Description	Features	Material	Standard Size
 <p>Access Door</p>	<ul style="list-style-type: none"> For easy access to ductwork maintenance and cleaning. Internal insulated to attenuate noise, prevent condensation and heat loss. 	<ul style="list-style-type: none"> Frame & Panel: 0.7mm galvanized steel. Seal: PE foam gasket. Door Lock: Aluminium or steel. Insulation: 25mm, 32kg/m³ fiber glass. Stud Rod: Galvanized Steel 	<ul style="list-style-type: none"> N300mm x 300mm N400mm x 400mm N450mm x 450mm Custom size available
 <p>Guide Vanes</p>	<ul style="list-style-type: none"> Minimize pressure drop and noise generated. Reduce turbulence. Energy saving. 	<ul style="list-style-type: none"> 1.0mm Galvanized Steel. 1.2mm Galvanized Steel. 	<ul style="list-style-type: none"> Custom size available
 <p>Ductwork Fittings</p>	<ul style="list-style-type: none"> Connection for ductwork. 	<ul style="list-style-type: none"> Thickness depend on ductwork. 	<ul style="list-style-type: none"> Custom size available
 <p>TD-C & TD-F Corner Piece</p>	<ul style="list-style-type: none"> Cost effective solution for ductwork connection. 	<ul style="list-style-type: none"> 1.0mm Galvanized Steel. 1.2mm Galvanized Steel. 	-
 <p>Stud & Threaded Rod</p>	<ul style="list-style-type: none"> Use for hanging ductwork. 	<ul style="list-style-type: none"> Galvanized Steel. 	<ul style="list-style-type: none"> Ø3/8 in (9.53mm) Ø1½ in (38.1mm)

Ductwork Accessories

Product Description	Features	Material	Standard Size
<div></div> <div>Quadrant Arm</div>	<ul style="list-style-type: none">• Volume control for manual volume damper.• With indicator.	<ul style="list-style-type: none">• 1.0mm Galvanized Steel.	-
<div></div> <div>Drop-in Anchor</div>	<ul style="list-style-type: none">• Used in medium to heavy duty application.• For solid concrete base material.• Ideal for overhead applications.• Fast, easy installation with excellent holding value.	<ul style="list-style-type: none">• Mild Steel.• Finishing: White Zinc Plated with half Knurling.	<ul style="list-style-type: none">• 5/16" x 10mm x 30mm• 3/8" x 12mm x 40mm